



KNOWLEDGE BASE

TOPIC: Installing the GECS Agent for OS/400

DATE: 12/13/2007

VERSION: 4.00



Copywrite 2007 Vinzant Software, Inc. All Rights Reserved.

All company and product names are trademarks, or registered trademarks, of their respective owners.

INSTALLING THE GECS AGENT FOR OS/400

A. Go to the computer running OS/400.

B. Login as QSECOFR

C. Enter

```
CRTLIB LIB(GECSLIB)
```

```
CRTSAVF FILE(GECSLIB/GECSSAVF)
```

D. Go to a computer running Windows.

E. Enter

```
MD C:\GECSFILE
```

F. Download the OS/400 Save File from the GECS web site as C:\GECSFILE\GECSSAVF

*** On the GECS web site, the file will have a six digit number appended to the name.

Save it on your system **without** the six digit number

G. Open a command shell (Start->Run->CMD.EXE)

H. Enter

```
C:
```

```
CD \GECSFILE
```

I. Start an FTP session with the computer running OS/400 by entering:

```
FTP computername
```

(where *computername* is the IP name or number of the computer running OS/400).

J. Login to the computer running OS/400 as QSECOFR

K Enter

```
BINARY
```

```
PUT GECSSAVF GECSLIB/GECSSAVF (REPLACE
```

Note that there is NO closing parenthesis on the above command.

```
QUIT
```

L. Go back to the computer that is running OS/400.

M. Enter

```
RSTLIB SAVLIB(GECSLIB) DEV(*SAVF) SAVF(GECSLIB/GECSSAVF)
```

To start the agent, enter:

```
SBMJOB CMD(call pgm(gecslib/gecsagnt) parm('-n agentname ' '-v')) ALWMLTTHD(*YES)
```